



**NATIONAL REFRIGERATION AND
AIR CONDITIONING CANADA CORP.**

159 ROY BLVD, PO BOX 2020
BRANTFORD, ON
CANADA N3T 5Y6

KLP532MA-S1B-T

**LOW PROFILE
EVAPORATOR**

PURCHASER :

SUBMITTED BY : **javier martinez**

PROJECT :

DATE : **12 Jan 2017**

ORDER # : **04394.41418.02282-000**

ITEM # : **1**

QUOTE # :

ID # :

PURCHASER'S PO # :

TAGGING :

MODEL FEATURES

- 3/8" Tubing coil construction (reduces refrigerant operating charge)
- Factory installed solenoid valve wire harness
- Heavy gauge textured aluminum cabinet construction resists scratches/corrosion
- Spacious piping end compartment allows for easy assembly
- Hinged drain pan with central universal drain connection (3/4" drain)
- Front access to spacious electrical and header compartments
- Schrader connection on suction header
- Attractive and durable high density polyethylene fan guards
- Ultra efficient Electronically Commutated Motor (ECM)
- ** ECM with SmartSpeed Technology
- High efficiency enhanced copper tube and aluminium fin coil design
- 6 FPI

MODEL OPTIONS (* = Shipped Loose)

PRE-ASSEMBLED EVAP

- Sporlan TXV, LLSV,T-stat
- Emerson TXV, LLSV,T-stat
- Danfoss TXV, LLSV, T-stat
- EEV Kit - Sporlan EEV + Kelvin II
- EEV Kit - Emerson EEV + EX48
- KE2 Demand Defrost w/Sporlan TXV
- KE2 Demand Defrost w/Sporlan EEV
- *KE2 Demand Defrost w/Sporlan TXV
- *KE2 Demand Defrost w/Sporlan EEV
- KE2 Demand Defrost w/KE2 EEV
- *KE2 Demand Defrost w/KE2 EEV

Aux Sideport Connector

CABINET FINISH

- Painted White
- Painted Black
- Stainless Steel

SENSORS FOR CPC I/O BOARDS

- Coil Temp Sensor
- Return Air Temp Sensor
- Suction Pressure Transducer

DEMAND DEFROST ELECTRONIC CONTROLLER

- KE2 Therm Evaporator Efficiency
- *KE2 Therm Evaporator Efficiency

Dual Circuit

ELECTRONIC CONTROLLER

- KE2 Temp+Defrost
- *KE2 Temp+Defrost

EXPANSION VALVE

- Sporlan TXV
- Emerson TXV
- Sporlan EEV
- Emerson EEV
- Danfoss TXV

SENSOR + TRANSDUCER FOR EEV

- for use with Emerson EEV
- Other Brand - Specify in Notes

ELECTRONIC SH CONTROLLER FOR EEV

- *Sporlan Kelvin II EEV Controller
- *Emerson EEV Controller
- *Other EEV Controller- Specify MFR Model in Notes

**Evaporator Disconnect Switch
EVAPORATOR PRISON PACKAGE**

- Tamper Proof Screws

**Export Crating
COIL COATING**

- Heresite Coating
- ElectroFin Coating

FIN AND MATERIAL

- Gold Coat Fins
- Copper Fins

Insulated Drain Pan

KE2 THERM

- *SmartGate Router #20695
- *8 Port Switch #20166
- *CAT5e Shielded Cable - 50ft w/connectors
- 40' Leads on Sensors + Transducers

***Liquid / Suction Heat Exchanger
LIQUID LINE SOLENOID VALVE**

- Danfoss
- Sporlan
- Emerson
- By Others Field Supplied

Dual Voltage Coil 120-230V Field Wired

Nitrogen Charged and Sealed ROOM THERMOSTATS

- Mechanical
- *Mechanical
- *Johnson A19ABC
- *Johnson A419ABC-1C
- Ranco ETC-111000
- *Ranco ETC-111000



Wire Fan Guards

REMOTE DEFROST PANEL

- *230V Control
- *115V Control

VOLTAGE	SYSTEM REFRIGERANT	AIR FLOW	EVAP. TEMP	BOX TEMP	CAPACITY
115/1/60	R404A	4500 CFM	25 °F	35 °F	32000 BTUH

FANS			HEATERS			CIRCUIT TOTAL			
QTY	POWER	FLA/FAN	TYPE	QTY	AMPS	AMPS	WATTS	MCA†	MOP‡
5	0.07HP	1				5	300	5.3	15

DISTRIBUTOR	1/2 in	SOUND	-	REC CAPACITY		APPROVALS
SUCTION	1 3/8 in	WEIGHT	163 lb	REF CHARGE	6 lb	 

NOTES:
† MCA.. Minimum Circuit Ampacity, ‡ MOP.. Maximum Overcurrent Protection

APPROVED BY :

DATE :

Approval of this drawing signifies that the equipment is acceptable under the provision of the job specifications. Any change made hereon by any person whomsoever subject to acceptance by NATIONAL REFRIGERATION at its home office.



**NATIONAL REFRIGERATION AND
AIR CONDITIONING CANADA CORP.**

159 ROY BLVD, PO BOX 2020
BRANTFORD, ON
CANADA N3T 5Y6

**Order Item No: 1
KLP532MA-S1B-T
LOW PROFILE
EVAPORATOR**

NATIONAL REFRIGERATION will furnish equipment in accordance with this drawing and specifications, and subject to its published warranty. Approval of this drawing signifies that the equipment is acceptable under the provision of the job specifications. Any change made hereon by any person whomsoever subject to acceptance by NATIONAL REFRIGERATION at its home office.



DATE : **12 Jan 2017**
PURCHASER :
PROJECT :
SUBMITTED BY : **javier martinez**

Dimensions shown are for standard unit less options.

DIMENSIONS	
DIMENSION A	94 1/4 in
DIMENSION B	32 5/8 in
DIMENSION C	48 5/8 in
DIMENSION D	
DIMENSION E	
DIMENSION F	
DIMENSION G	0 in
DIMENSION H	

CONNECTIONS	
DISTRIBUTOR	1/2 in
SUCTION	1 3/8 in
DRAIN	3/4 in
WATER	
DISCHARGE	
PAN LOOP	
HOT GAS SIDE PORT	
HOT GAS INLET	
HOT GAS OUTLET	
OTHER	
SHIPPING WEIGHT	163 lb
REFRIGERANT CHARGE	6 lb
RECEIVER CAPACITY	

APPROVALS			



NOTES: